



### **DUAL SLIDING DOOR**

The Dual Sliding Containment Door is highly dependable and unbelievably versatile. A simple and streamlined design allows an extremely low profile and an unparalleled level of customization. With key standard features and a wide range of available options, you can be sure that you will get exactly what you need for your hot or cold containment system.

### STANDARD FEATURES

- > Custom Sized (to 1/8")
- > Rigid Design
- > No Threshold
- > Auto-Closing
- > Soft-Closing
- > Hold-Open
- > Modular Design
- > Clear or Black Anodized







Auto-Closing

Customizable







## DUAL SLIDING DOOR PRODUCT SPECIFICATIONS

# FRAMEWORK Aluminum Extrusion Tensile Strength 27,000 PSI

INSERTS		
Varies	Flame Rating	Varies by chose insert option. (See examples below.)
8mm Twinwall Polycarbonate	Flame Rating	ASTM E84 Class A
3mm Clear Acrylic	Flame Rating	UL 94 HB

<sup>\*</sup>Additional Insert Options Available

#### **CUSTOMIZABLE OPTIONS**

- > Insert Material Options\*
- > Powder-Coated Finish
- > Custom Designs and Logos
- > Extra Large Options Available
- Max Frame Size: 100" W x 100" H